



TSI 02/2020

Anaerobe Dichtmassen

| | EL-Loc 43 | EL-Loc 70 | EL-Liq 73 | EL-Liq 74 | EL-Add 48 | EL-Fil 77 |
|----------------------------------|------------------------------------|------------------------------------|---------------------------|--------------------------|---------------------------|---------------------------|
| | 700.501 10 ml 954.000 50 ml | 700.521 10 ml 954.010 50 ml | 777.792 50 ml | 461.682 50 ml | 954.030 50 ml | 954.020 50 ml |
| | | | ≤ 0,35 mm | ≤ 0,35 mm | ≤ 0,25 mm | ≤ 0,35 mm |
| | M 36 | M 20 | M 80 | M 80 | | M 80 |
| | 15 - 25 N/mm ² | 30 - 40 N/mm ² | 10 - 20 N/mm ² | 5 - 10 N/mm ² | 35 - 55 N/mm ² | 25 - 35 N/mm ² |
| | ++ | + | ++ | ++ | + | ++ |
| | 5 - 15 min | 5 - 15 min | 10 - 20 min | 5 - 15 min | 5 - 15 min | 10 - 20 min |
| | 2k - 4k mPa/s | 300 - 900 mPa/s | 35k - 60k mPa/s | 30k - 200k mPa/s | 400 - 700 mPa/s | 15k - 30k mPa/s |
| Allgemein General information | | | ready to service 2 - 3h | | -55 °C - +180 °C | |
| | | | | | | |

ElringKlinger AG | Geschäftsbereich Ersatzteile
 Max-Eyth-Straße 2 | D-72581 Dettingen/Erms
 Fon +49 7123 724-799 | Fax +49 7123 724-798
 service@elring.de | www.elring.com

